

therm-x2® Profilato-K sostitutivo  
Resa termica a norma in Watt



Temperatura ambiente 20°C  
Temperatura dell'acqua di riscaldamento 75/65°C

Altezza mm		554			954		
	Tipo	12	22	33	12	22	33
Larghezza mm	Watt/m 75/65°C	1153	1564	2252	1786	2307	3218
400	W 75/65°C	461	626	901	714	923	1287
500	W 75/65°C	577	782	1126	893	1154	1609
600	W 75/65°C	692	938	1351	1072	1384	1931
700	W 75/65°C	807	1095	1577	1250	1615	2253
800	W 75/65°C	922	1251	1802	1429	1846	2575
900	W 75/65°C	1038	1408	2027	1608	2076	2896
1000	W 75/65°C	1153	1564	2252	1786	2307	3218
1100	W 75/65°C	1268	1721	2477	1965	2538	3540
1200	W 75/65°C	1384	1877	2703	2143	2769	3862
1300	W 75/65°C	1499	2033	2928	2322	2999	4184
1400	W 75/65°C	1614	2190	3153	2501	3230	4506
1600	W 75/65°C	1845	2503	3603	2858	3691	5149
1800	W 75/65°C	2076	2815	4054	3215	4153	5793
2000	W 75/65°C	2306	3128	4504	3572	4614	6436
2300	W 75/65°C	2652	3597	5180	4108	5307	7402
2600	W 75/65°C	2998	4067	5856	4644	5999	8367
3000	W 75/65°C	3459	4692	6757	5358	6922	9655

Interasse 350 mm (altezza 400 mm) vedere tabella radiatori compatti profilati